

## AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listing of claims in the application.

### **Listing of Claims**

1. (previously presented) A ball mill, comprising:  
a tubular vessel for containing grinding media and a material to be ground, the tubular vessel having an axis;  
a drive mechanism including a drive rod that induces a linear reciprocating movement of the tubular vessel substantially along the axis of the vessel to grind the contained material by moving the grinding media back and forth within the tubular vessel; and  
an air bearing supporting substantially frictionless reciprocating movement of the drive rod.
2. (original) The ball mill as in claim 1 wherein the linear reciprocating movement occurs at a rate in excess of 1000 cycles per second.
3. (original) The ball mill as in claim 1 wherein the linear reciprocating movement produces a stroke distance in excess of 1 inch.
4. (original) The ball mill as in claim 1 wherein the axis of the tubular vessel is substantially vertically oriented.
5. (original) The ball mill as in claim 1 wherein the axis of the tubular vessel is substantially horizontally oriented.
6. (original) The ball mill as in claim 1 wherein the grinding media comprises a single ball having a diameter that is less than an inner diameter of the tubular vessel.

7. (previously presented) The ball mill as in claim 6 wherein ends of the tubular vessel are defined by a spherical surface conforming to the inner diameter of the tubular vessel.

8. (original) The ball mill as in claim 7 wherein the spherical surface is hemispherical.

9. (original) The ball mill as in claim 1 wherein the grinding media comprises a plurality of balls.

10. (original) The ball mill as in claim 9 wherein the plurality of balls are of differing sizes.

11. (original) The ball mill as in claim 1 wherein the grinding media comprises a single cylindrical slug having a diameter that is less than an inner diameter of the tubular vessel.

12. (original) The ball mill as in claim 11 wherein ends of the tubular vessel are defined by a flat surface.

13. (original) The ball mill as in claim 11 wherein ends of the tubular vessel are defined by a conical surface.

14. (previously presented) The ball mill as in claim 1 further including:  
a platform supporting the tubular vessel; and  
the drive rod passing through the air bearing and transferring the induced linear reciprocating movement to the platform supporting the tubular vessel.

15. (canceled).

16. (previously presented) The ball mill as in claim 1 wherein the axis of the tubular vessel is offset from a direction of the induced linear reciprocation by an acute angle.

17. (previously presented) A ball mill, comprising:  
a sample holder comprised of a plurality of vessels, each vessel having a tubular configuration and a longitudinal axis about which an interior for performing ball grinding is defined; and

means for reciprocating a drive rod coupled to the sample holder in a substantially frictionless manner and in a direction substantially parallel to axes of the plurality of vessels within the same holder.

18. (previously presented) The ball mill as in claim 17 wherein the means for reciprocating comprises a vertically reciprocating drive mechanism having the drive rod which induces reciprocating movement of the sample holder substantially along the longitudinal axes of the vessels.

19. (previously presented) The ball mill as in claim 17 wherein the means for reciprocating comprises a horizontally reciprocating drive mechanism having the drive rod which induces reciprocating movement of the sample holder substantially along the longitudinal axes of the vessels.

20. (original) The ball mill as in claim 17 further including a dampening base.

Claims 21-32. (canceled).

33. (previously presented) A ball mill grinding method, comprising the steps of:  
loading a vessel with a grinding media and a material to be ground, the vessel having a longitudinal axis;  
capping the vessel to contain the grinding media and material; and

reciprocating a shaft of a drive mechanism coupled to the capped vessel containing the grinding media and material to be ground in a substantially frictionless manner and in a direction substantially along the longitudinal axis.

34. (original) The ball mill grinding method as in claim 33 wherein the step of reciprocating comprises the step of reciprocating with a vertical orientation.

35. (original) The ball mill grinding method as in claim 33 wherein the step of reciprocating comprises the step of reciprocating with a horizontal orientation.

36. (original) The ball mill grinding method as in claim 33 wherein the step of loading comprises the step of loading a single ball within the vessel.

37. (original) The ball mill grinding method as in claim 33 wherein the step of loading comprises the step of loading a plurality of balls within the vessel.

38. (original) The ball mill grinding method as in claim 37 wherein the plurality of balls are of differing sizes.

39. (original) The ball mill grinding method as in claim 33 wherein the step of loading comprises the step of loading a single cylindrical slug within the vessel.

40. (previously presented) The ball mill as in claim 17, wherein the means for reciprocating comprises an air bearing supporting substantially frictionless movement of the drive rod.

41. (previously presented) The ball mill as in claim 17, wherein the means for reciprocating comprises an air bearing supporting substantially frictionless movement of the drive rod.